

MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

MANUFACTURING SITE: FAIRWAY BUILDING PRODUCTS

ADDRESS: PO BOX 37, 53 EBY CHIQUES RD, MOUNT JOY, PA 17552

TRADE NAME: FAIRWAY VINYL SYSTEMS

SYNONYMS: VINYL DECK, RAILING AND FENCE

TELEPHONE NUMBER: (717) 653-6777

2. COMPONENTS AND HAZARD CLASSIFICATION

PVC Polymer	70-95%	
Inert Fillers	0-30%	CaCO ₃ TiO ₂
Heat Stabilizer	0-2%	Organotin Compounds
Lubricants	0-4%	Calcium Stearate; Paraffin, Polyethylene, Polyamide Compounds or Esters
Process Aids	0-2%	Acrylic Compounds
Impact Modifiers	0-10%	ABS, or Acrylic Compounds
Colorants	0-2%	Organic and inorganic Colorants (may contain heavy metals in the form of mixed metals oxides)

- PVC profiles typically contain less than 0.15ppm RVCN, and in no case contain greater than 1.0ppm residual vinyl chloride monomer.
- Contains no chemicals subject to SARA 302 or SARA 311/312 reporting.
- PVC profiles contain zero lead or Antimony Compounds.
- PVC accessories contain zero lead and no greater than 1.5% Antimony Compounds which is a chemical subject to SARA 313 reporting

3. PHYSICAL DATA

BOILING POINT: SOLID

SPECIFIC GRAVITY (H₂O=1): 1.40 – 1.48

VAPOR PRESSURE (mm Hg.): : SOLID

MELTING POINT: Decomposes before melting

SOLUBILITY IN WATER : SOLID

VAPOR DENSITY: SOLID

APPEARANCE AND ODOR: SOLID, NO ODOR

4. FIRE AND EXPLOSION DATA

FLASH POINT: 900 DEGREES

AUTOIGNITION TEMP: N/A

FLAMMABLE LIMITS IN AIR % BY VOL.

LOWER: N/A

UPPER: N/A

EXTINGUISHING MEDIA: WATER SPRAY, FOAM, DRY CHEMICAL OR CO₂

SPECIAL FIRE FIGHTING PROCEDURES: Cool exposed equipment with water spray. Use self contained apparatus if fighting fire in confined spaces.

UNUSUAL FIRE AND EXPLOSION HAZARD: Prior to extrusion and in its raw form, PVC contains less than 1.0ppm vinyl chloride monomer and evolves hydrogen chloride, carbon monoxide, and other toxic gases when burned. Exposure to combustion products may be fatal and should be avoided. PVC extrusion process removes potentially harmful volatile through heat, compression and concentrated vacuum. <1.0 ppm Vinyl Chloride monomer remains with in profiles.

5. HEALTH HAZARD INFORMATION

FIRST AID

- EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if irritation persists.
- SKIN:** Flush with water to remove material from skin.
- INHALATION:** Remove to fresh air.
- INGESTION:** If swallowed, call a physician immediately. ONLY induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

NATURE OF HAZARD

Cutting of PVC profiles result in the generation of sawdust. The dust is classified as a nuisance dust. Exposure to the dust may cause physical irritation of contacted areas.

PVC, in its raw form, under burning condition, HCL gas will be produced. HCL gas is irritating to the upper respiratory tract. Exposure to high concentrations of HCL gas may be fatal.

The extrusion process heats, compresses, and evacuates the HCL gas. PVC extrusions, according to OSHA, are not classified as hazardous.

EXPOSURE LIMITS

NUISANCE DUST: OSHA PEL of 15mg/m³ TWA* for 8 hours.
ACGIH TLV of 10mg/m³ TWA for 8 hours.

VINYL CHLORIDE: OSHA PEL of 1.0 ppm TWA for 8 hours; 5 ppm for 15-minute TWA.
ACGIH TLV of 5.0 ppm for 8 hours.

* TWA = Time Weighted Average

TOXICITY DATA

- SKIN CONTACT:** A review of the pertinent literature did not reveal specific information for PVC.
- EYE CONTACT:** A review of the pertinent literature did not reveal specific information for PVC.
- INHALATION:** Rodents exposed by the dietary or inhalation route for 6 to 24 months have shown no significant toxicological effects.
- INGESTION:** See Above

SPECIAL PRECAUTIONS

AVOID INHALATION OF COMBUSTION PRODUCTS.

6. REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY:

N/A

INCOMPATIBILITY:

N/A

HAZARDOUS DECOMPOSITION PRODUCTS:

Hydrogen chloride and other toxic fumes generated with combustion.

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:

N/A

7. SPILL OR LEAK PROCEDURES

In case of spill, sweep, scoop, or vacuum and remove. Dispose of in accordance with local, state, and federal regulations as applicable.

8. SPECIAL PROTECTION INFORMATION

VENTILATION RECOMMENDATIONS

General ventilation for thermal processing and nuisance dust control.

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION:

If dust is produced during cutting, an approved particulate filter respirator should be used.

EYES:

Safety glasses or goggles.

GLOVES:

Necessary when handling hot or molten material.

Other clothing and equipment:

As necessary when handling hot or molten material.

9. SHIPPING, TRANSFER AND STORAGE

SHIPPING INFORMATION

This product is not a hazardous material or hazardous substance as defined by the Department of Transportation, nor is it a dangerous good as defined by IATA for air transportation or IMO for Marine Transport.

TRANSPORTATION AND STORAGE

USUAL SHIPPING CONTAINERS:

Poly film shrink plastic cover w/wood bundle supports

STORAGE/TRANSPORT TEMPERATURE:

Exposure to ambient temperature variation is acceptable. Care should be given to flat profile storage. To prevent shape deformation, electrostatic accumulation or its presence is a potential.

Certain applications may require the use of a Quaternary Ammonium as a suppressant.

ELECTROSTATIC ACCUMULATION HAZARD:

HANDLING AND STORAGE MATERIALS AND COATINGS

SUITABLE:

Non abrasive or reactive contact surfaces.

THE ABOVE DATA IS BASED ON TESTS AND EXPERIENCE WHICH FAIRWAY BUILDING PRODUCTS BELIEVES RELIABLE AND ARE SUPPLIED FOR INFORMATIONAL PURPOSES ONLY. FAIRWAY BUILDING PRODUCTS PRODUCTS ARE INTENDED FOR SALE TO INDUSTRIAL AND COMMERCIAL CUSTOMERS. FAIRWAY BUILDING PRODUCTS REQUESTS THAT CUSTOMERS INSPECT AND TEST OUR PRODUCTS BEFORE USE AND SATISFY THEMSELVES AS TO CONTENTS AND SUITABILITY. FAIRWAY BUILDING PRODUCTS DISCLAIMS ANY LIABILITY FOR DAMAGE OR INJURY WHICH RESULTS FROM THE USE OF THE ABOVE DATA AND NOTHING CONTAINED THEREIN SHALL CONSTITUTE A GUARANTEE WARRANTY (INCLUDING WARRANTY OF MERCHANTABILITY) OR REPRESENTATION (INCLUDING FREEDOM FROM PARENT LIABILITY) BY FAIRWAY BUILDING PRODUCTS WITH RESPECT TO THE DATA, THE PRODUCT DESCRIBED, OR THEIR USE FOR ANY SPECIFIC PURPOSE, EVEN IF THAT PURPOSE IS KNOWN TO FAIRWAY BUILDING PRODUCTS.